


SINGLE ROW DEEP GROOVE BALL BEARINGS



Z



ZZ



RS



2RS



N




NR

Bore Diameter d(mm)	Outer Diameter D(mm)	Open Brgs Width B(mm)	Item No.	Weight kg
10	15	3	6700	0.0015
	19	5	6800	0.005
	22	6	6900	0.009
	26	8	6000	0.019
	28	8	16100	0.022
	30	9	6200	0.032
	35	11	6300	0.053
12	18	4	6701	0.003
	21	5	6801	0.006
	24	6	6901	0.011
	28	7	16001	0.019
	28	8	6001	0.021
	30	8	16101	0.023
	32	10	6201	0.037
37	12	6301	0.060	
15	21	4	6702	0.0035
	24	5	6802	0.007
	28	7	6902	0.016
	32	8	16002	0.025
	32	9	6002	0.030
	35	11	6202	0.045
	42	13	6302	0.082
17	23	4	6703	0.004
	26	5	6803	0.008
	30	7	6903	0.018
	35	8	16003	0.032
	35	10	6003	0.039
	40	12	6203	0.066
	47	14	6303	0.115
20	27	4	6704	0.005
	32	7	6804	0.019
	37	9	6904	0.036
	42	8	16004	0.051
	42	12	6004	0.069
47	14	6204	0.106	

Bore Diameter d(mm)	Outer Diameter D(mm)	Open Brgs Width B(mm)	Item No.	Weight kg
20	52	15	6304	0.144
	72	19	6404	0.400
22	44	12	60/22	0.074
	50	14	62/22	0.117
	56	16	63/22	0.176
25	32	4	6705	0.006
	37	7	6805	0.022
	42	9	6905	0.042
	47	8	16005	0.060
	47	12	6005	0.080
	52	15	6205	0.128
28	62	17	6305	0.232
	80	21	6405	0.530
	52	12	60/28	0.098
	58	16	62/28	0.171
	68	18	63/28	0.284
	37	4	6706	0.008
30	42	7	6806	0.026
	47	9	6906	0.048
	55	9	16006	0.091
	55	13	6006	0.006
	62	16	6206	0.199
32	72	19	6306	0.360
	90	23	6406	0.735
	58	13	60/32	0.129
	65	17	62/32	0.226
35	75	20	63/32	0.382
	47	7	6807	0.029
	55	10	6907	0.074
	62	9	16007	0.110
	62	14	6007	0.155
	72	17	6207	0.288
	80	21	6307	0.457
40	100	25	6407	0.952
	52	7	6808	0.033
	62	12	6908	0.110

Bore Diameter d(mm)	Outer Diameter D(mm)	Open Brgs Width B(mm)	Item No.	Weight kg
40	68	9	16008	0.125
	68	15	6008	0.190
	80	18	6208	0.366
	90	23	6308	0.630
	110	27	6408	1.230
45	58	7	6809	0.040
	68	12	6909	0.128
	75	10	16009	0.171
	75	16	6009	0.237
	85	19	6209	0.398
50	100	25	6309	0.814
	120	29	6409	1.530
	65	7	6810	0.052
	72	12	6910	0.132
	80	10	16010	0.180
55	80	16	6010	0.261
	90	20	6210	0.454
	110	27	6310	1.070
	130	31	6410	1.880
	72	9	6811	0.083
60	80	13	6911	0.180
	90	11	16011	0.258
	90	18	6011	0.388
	100	21	6211	0.601
	120	29	6311	1.370
65	140	33	6411	2.290
	78	10	6812	0.106
	85	13	6912	0.193
	95	11	16012	0.283
	95	18	6012	0.414
70	110	22	6212	0.783
	130	31	6312	1.730
	150	35	6412	2.770
	85	10	6813	0.128
75	90	13	6913	0.206
	100	11	16013	0.307

SINGLE ROW DEEP GROOVE BALL BEARINGS



Z



ZZ



RS



2RS



N



NR

Bore Diameter d(mm)	Outer Diameter D(mm)	Open Brgs Width B(mm)	Item No.	Weight kg
65	100	18	6013	0.421
	120	23	6213	0.990
	140	33	6313	2.080
	160	37	6413	3.300
70	90	10	6814	0.137
	100	16	6914	0.334
	110	13	16014	0.441
	110	20	6014	0.604
	125	24	6214	1.070
	150	35	6314	2.520
180	42	6414	4.830	
75	95	10	6815	0.145
	105	16	6915	0.353
	115	13	16015	0.464
	115	20	6015	0.649
	130	25	6215	1.180
	160	37	6315	3.020
	190	45	6415	5.720
80	100	10	6816	0.154
	110	16	6916	0.373
	125	14	16016	0.597
	125	22	6016	0.854
	140	26	6216	1.400
	170	39	6316	3.590
	200	48	6416	6.760
85	110	13	6817	0.270
	120	18	6917	0.536
	130	14	16017	0.626
	130	22	6017	0.890
	150	28	6217	1.790
	180	41	6317	4.230
210	52	6417	7.950	
90	115	13	6818	0.285
	125	18	6918	0.554
	140	16	16018	0.848

Bore Diameter d(mm)	Outer Diameter D(mm)	Open Brgs Width B(mm)	Item No.	Weight kg
90	140	24	6018	1.020
	160	30	6218	2.150
	190	43	6318	4.910
	225	54	6418	11.400
95	120	13	6819	0.300
	130	18	6919	0.579
	145	16	16019	0.885
	145	24	6019	1.080
	170	32	6219	2.620
200	45	6319	5.670	
100	125	13	6820	0.313
	140	20	6920	0.785
	150	16	16020	0.910
	150	24	6020	1.150
	180	34	6220	3.140
	215	47	6320	7.000
105	130	13	6821	0.330
	145	20	6921	0.816
	160	18	16021	1.200
	160	26	6021	1.590
	190	36	6221	3.700
110	140	16	6822	0.515
	150	20	6922	0.849
	170	19	16022	1.460
	170	28	6022	1.960
	200	38	6222	4.360
	240	50	6322	9.540
120	150	16	6824	0.555
	165	22	6924	1.150
	180	19	16024	1.560
	180	28	6024	2.070
	215	40	6224	5.150
260	55	6324	12.400	
130	165	18	6826	0.800

Bore Diameter d(mm)	Outer Diameter D(mm)	Open Brgs Width B(mm)	Item No.	Weight kg
130	180	24	6926	1.520
	200	22	16026	2.310
	200	33	6026	3.160
	230	40	6226	5.820
	280	58	6326	15.300
140	175	18	6828	0.850
	190	24	6928	1.620
	210	22	16028	2.450
	210	33	6028	3.350
	250	42	6228	7.570
300	62	6328	18.500	
150	190	20	6830	1.160
	210	28	6930	2.470
	225	24	16030	3.070
	225	35	6030	4.080
	270	45	6230	9.410
	320	65	6330	22.000
160	200	20	6832	1.230
	220	28	6932	2.610
	240	25	16032	3.640
	240	38	6032	5.05
	290	48	6232	11.700
	340	68	6332	26.000
170	215	22	6834	1.630
	230	28	6934	2.74
	260	28	16034	4.930
	260	42	6034	6.760
	310	52	6234	14.500
	360	72	6334	30.700
180	225	22	6836	2.030
	250	33	6936	4.760
	280	31	16036	6.490
	280	46	6036	8.800
	320	52	6236	15.100
	380	75	6336	35.600